

DEAFGARD



The deaf and hard of hearing are in danger of not hearing your fire alarm. Deafgard is the safe, legal and cost-effective solution.



The **Deafgard Series** provides a wire-free solution for communicating the sounding of the fire alarm to deaf and hard of hearing people.

Deafgard features

- *No installation required*
- *Wire-free technology*
- *Automatically activates when the fire alarm sounds*
- *Fail-to-safe dual battery supply*
- *Alarm clock facility for the deaf and hard of hearing*

Deafgard

Deafgard is a moveable wire-free, acoustically-triggered bedside unit that incorporates a high-intensity strobe and a connected vibrator pad, that when placed under the pillow, vibrates to wake the sleeper upon the fire alarm sounding.

A flashing strobe and LCD provide visual indication that the fire alarm is sounding, allowing the individual to leave their room to a place of safety.



TECHNICAL SPECIFICATIONS

Dimensions and weight

- Overall height: 4.52in.
- Main casing height: 2.16in.
- Width: 6.50in.
- Depth: 4.90in.
- Packed kit weight: 2.13lb.
- Product only (including batteries): 1.85lb.

Material and operating specifications

- Casing: ABS
- Power: 4 x 1.5v C size alkaline batteries (do not use rechargeable batteries)
- Expected battery life: 12 months

ALSO AVAILABLE FROM SDi

- **Professional Smoke Detector Testers**
with approved and listed dispensers
- **Genuine Professional Heat Detector Testers**
suitable for fixed temperature, rate of rise and combined detectors
- **CO Detector Testers**
with approved and listed dispenser
- **Aerosol Dispensing Tools**
as recommended by detector manufacturers
- **Detector Removal Tools**
suitable for all leading makes and model of detector
- **Access Poles**
to enable detector maintenance up to 30+ ft.
- **Complete Maintenance and Service**
providing complete solutions in economical and convenient kit formats
- **Smoke Detector Sensitivity Instruments**
to identify sensitivity drift and help ensure that smoke detector sensitivity is maintained within defined calibration parameters



Specialized Fire Products

SDi,
1345 Campus Parkway, Neptune, NJ 07753-6815 USA
Tel: 732-751-9266 Fax: 732-751-9241
Email: sales@sdifire.com Web: www.sdifire.com